## Contact No. 194 M2100 Toggles & Rockers

## Change of Red/Green Bicolor LED Specification

Type of Change:

✓ Engineering✓ Part Number✓ Product✓ Appearance

The LED specifications for M2100 toggle & rocker switches (not paddles) with red/green bicolor LED will change.

This change will affect all M2100 toggle & rocker switches with red/green bicolor LED including all custom products.

Bicolor LED Specifications						
			From Current Bicolor LED		To New Bicolor LED	
LEDs are an integral part of the switch and are not available separately. Bicolor is white in OFF state.			F	C	F	C
		Color	Green	Red	Green	Red
	Forward Peak Current	l <sub>FM</sub>	25mA	25mA	25mA	25mA
	Continuous Forward Current	l <sub>F</sub>	10mA	10mA	10mA	10mA
	Forward Voltage	$V_{_{\rm F}}$	1.9V	1.9V	2.0V	1.7V
	Current Reduction Rate Above 25°C	$\Delta_{IF}$	0.33 mA/°C	0.33 mA/°C	0.33 mA/°C	0.33 mA/°C
	Ambient Temperature Range	Ta	−10°C ~ +55°C		−10°C ~ +55°C	

- · No change to dimensions.
- · Forward Voltage will be changed. Please make sure to use appropriate resistor.
- · Contact factory for further details.

## **Effective Date**

Change will be effective with December 2011 production.



NIHON KAIHEIKI IND. CO., LTD.

715-1 Unane, Takatsu-ku, Kawasaki-shi, 213-8553, Japan Telephone +81-44-813-8008 • Fax +81-44-813-8038